



Specs:8 3/4" WS516DT(222.25mm)

IADC:S423

ID:WFN222S16523A



Design character:

- Dual-row cutters. The back row cutters help to cut rocks, to protect matrix, to prolong lifetime and to deduct cost of PDC bit.
- Straight blade and short gauge: When pumping pressure is low abrasive drilling mud can be discharged quickly to avoid bit balling and losing efficacy of bit.
- Long parabolic profiles PDC bit cut rock greatly, have faster ROP. This design suit for rotary drilling in soft and low abrasive formation.
- Suit for well drilling in low compressive strength, even texture medium rock formation. Such as wake shale, density marlstone, strong batt, wake sandstone, limestone, and soft gravel, etc.

Specialized for oil/gas well design ,high speed drilling & long life-span using

Specifications:

Blade Qty	5
Total Cutters	59
Primary Cutter Size	16mm
Assistant Cutter Size	13.44mm
Gauge Cutter Size	13.44mm
anti-quake ball size	Non
Nozzle Qty.	6
Crown length	152mm
Gauge length	63mm
Connetion Size	4 1/2REG
Make-up Torque	16.63—23.71kN.m
Assembly groove wID:th	145mm
Bit Weight	47.6kg

Operating Parameters:

Rotary speed	60-260RPM
Flow rate	28-40L/S
Weigh on bit	20-100KN